

GAS COOKTOPS

RDGSU200 – 30" WIDE

RDGSU260 – 36" WIDE



Features and Functions

- Wide variety of BTU ratings to accommodate all types of surface cooking needs
 - 30" wide model – NEW – 5 burners
 - Left front – 9,100 BTU
 - Left rear – 9,100 BTU
 - Center – 17,000 BTU (dual stacked burner)
 - Right front – 12,000 BTU
 - Right rear – 5,000 BTU
 - 36" wide model
 - Left front – 9,100 BTU
 - Left rear – 9,100 BTU
 - Center – 17,000 BTU (dual stacked burner)
 - Right front – 12,000 BTU
 - Right rear – 5,000 BTU
- Sealed burners with aluminum flame ports and porcelainized, cast-iron burner caps
- Automatic electronic spark ignition/re-ignition; burners light at any position on the knob and re-light if extinguished, even at lowest setting

Easy Operation and Cleanup

- Permanently sealed burners – spills cannot enter burner box
- One-piece, extremely durable steel top with separate spill collection areas
- Durable, metal die-cast knobs with child-proof, push-to-turn safety feature
- Customer-removable knobs, grates, and burners/caps for easy cleaning
- Grate design provides continuous surface for easy movement of pots
- Overall/burner box dimensions designed to fit majority of similarly sized cooktop cutouts

Installation Accessories

- LP conversion kit

Finishes


- Available in Stainless Steel (SS)
 - Finish designates top; all units have black porcelain grates and burner caps

Customizable Options


- Shipped standard with chrome knob inserts
- Create your own look with customizable knob inserts
- Accessory kits available in the following finishes:
 - Paintable clear plastic
 - Wood – cherry, oak, maple, and unfinished maple (can be stained to match existing cabinetry)

Warranty Highlights

- Three-year full – complete unit
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – stainless steel exterior
- Five-year limited – surface burners



30" Wide Gas Cooktop



36" Wide Gas Cooktop

DESCRIPTION	GAS 30" AND 36" WIDE COOKTOPS	
	RDGSU200	RDGSU260
Overall Width	30 3/4" (78.1 cm)	36 3/4" (93.3 cm)
Overall Height	4 3/8" (13.7 cm)	
Overall Depth	21" (53.3 cm)	
Cutout Width	29 1/4" (74.3 cm) minimum 29 7/8" (75.9 cm) maximum	35 1/4" (89.5 cm) minimum 35 7/8" (91.1 cm) maximum
Cutout Height	3 1/8" (7.9 cm)	
Cutout Depth	20" (50.8 cm) minimum; 20 1/4" (51.4 cm) maximum	
Gas Requirements	Ships Natural or LP/Propane; Field convert with conversion kit (purchased separately); accepts standard residential 1/2" (1.3 cm) ID gas service line.	
Electrical Requirements	120VAC/60Hz; 4 ft. (121.9 cm), 3-wire cord with grounded 3-prong plug attached to product	
Maximum Amp Usage	2.0 amps	
Surface Burner Rating	Left Front – 9,100 BTU Left Rear – 9,100 BTU Center – 17,000 BTU Right Front – 12,000 BTU Right Rear – 5,000 BTU	Left Front – 9,100 BTU Left Rear – 9,100 BTU Center – 17,000 BTU Right Front – 12,000 BTU Right Rear – 5,000 BTU
Approximate Shipping Weight	49 lb. (22.0 kg)	74 lb. (33.3 kg)



Viking Range Corporation • 111 Front Street • Greenwood, Mississippi 38930 USA • (662) 455-1200
For product information, call 1-888-VIKING1 (845-4641), or visit the Viking website at vikingrange.com.



© 2012, Viking Range Corporation • Specifications subject to change without notice.