GAS SELF-CLEAN RANGE

RDSCG230-5B - 30" WIDE



Features and Functions

- Wide variety of BTU ratings to accommodate all types of surface cooking needs – including a NEW fifth burner
- Left front 18,000 BTU (dual stacked burner)
- Left rear 8,000 BTU
- Center 9,000 BTU
- Right front 17,000 BTU
- Right rear 12,000 BTU
- Sealed burners with porcelainized, cast-iron burner caps
- Exclusive SureSparkTM Ignition System
- Automatic electric spark ignition/re-ignition; surface burners light at any position on the knob and re-light if extinguished, even on lowest setting
- Large-capacity oven has six porcelain-coated rack supports and comes standard with two TruGlideTM full extension oven racks and one standard rack.
- High performance cooking modes include Natural Airflow Bake, Convection Bake, Broil, Convection Broil, Convection Dehydrate, and Convection Defrost
- All convection functions utilize the ProFlowTM Convection Air Baffle, which is specifically designed to ensure balanced air flow for even heat distribution
- Exclusive combination of single 30,000 BTU U-shaped burner and broiler with SureSparkTM Ignition System

30" Wide Gas Self-Clean Range (Shown with optional 6" H. backguard.)

- 15,000 BTU broiler provides intense searing heat for broiling applications
- Heavy-duty broiler pan and tray provide better broiling performance
- Two halogen oven lights for excellent visibility throughout oven cavity
- Shipped standard with island trim

Easy Operation and Cleanup

- Extremely large self-clean convection oven
- Permanently sealed burners spills cannot enter the one-piece, tooled and porcelainized burner box
- Durable metal die-cast knobs with child-proof, push-to-turn safety feature
- Customer-removable knobs, grates, and burners/caps for easy cleaning
- Grate design provides continuous cooking surface for easy movement of pots and pans

Installation Accessories

- 6" high backguard
- High shelf
- Countertop side trim
- Countertop rear trim
- Curb base and custom curb base front
- LP conversion kit

Exclusive Finishes

 Available in Stainless Steel (SS), Black (BK), White (WH), Apple Red (AR), Burgundy (BU), Cinnamon (CN), Cobalt Blue (CB), Dijon (DJ), Graphite Gray (GG), Stone Gray (SG), Viking Blue (VB), and Wasabi (WS)

Customizable Options

- Shipped standard with chrome knob and handle inserts
- Create your own look with customizable knob and handle inserts
- Accessory kits available in the following finishes:
- Paintable clear plastic
- Wood cherry, oak, maple, and unfinished maple (can be stained to match existing cabinetry)

Warranty Highlights

- Three-year full complete unit
- Ninety-day full cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited stainless steel exterior
- Ten-year limited porcelain oven
- Five-year limited surface/tube burners



DESCRIPTION	GAS SELF-CLEAN 30" WIDE RANGE
DESCRIPTION	RDSCG230-5B
Overall Width	29 7/8" (75.9 cm)
Overall Height	To top of side trim – 35 7/8" (91.1 cm) minimum; 37" (94.0 cm) maximum Legs adjust – 1 1/8" (2.9 cm)
Overall Depth from Rear	To front of side panel – 25" (63.5 cm) To front of door – 25 3/4" (65.4 cm) To front of control panel – 27 1/8" (68.9 cm) To end of knobs – 29" (73.7 cm)
Additions to Overall Height	To top of island trim – add 0" (0.0 cm) To top of 6" high backguard – add 6" (15.2 cm) To top of high shelf – add 18 3/16" (46.2 cm)
Gas Requirements	Ships Natural or LP/Propane; Field convert with conversion kit (purchased separately); accepts standard residential 1/2" (1.3 cm) ID gas service line.
Gas Manifold Pressure	Natural 5.0" W.C.P./Liquid Propane L/P 10.0" W.C.P.
Electrical Requirements	120VAC/60Hz; 4 ft. (121.9 cm), 3-wire cord with grounded 3-prong plug attached to unit
Maximum Amp Usage	.74 amps
Surface Burner Rating Natural/LP	Left Front: 18,000 BTU Nat./15,800 BTU LP/Propane (5.3 kW Nat./4.7 kW LP/Propane) Left Rear: 8,000 BTU Nat./6,500 BTU LP/Propane (2.3 kW Nat./1.9 kW LP/Propane) Center: 9,000 BTU Nat./8,000 BTU LP/Propane (2.7 kW Nat./2.3 kW LP/Propane) Right Front: 17,000 BTU Nat./15,000 BTU LP/Propane (5.0 kW Nat./4.4 kW LP/Propane) Right Rear: 12,000 BTU Nat./11,000 BTU LP/Propane (3.5 kW Nat./3.2 kW LP/Propane)
Oven Interior Width	23" (58.4 cm)
Oven Interior Height	16 1/8" (40.9 cm)
Oven Interior Depth	Overall – 18 3/4" (47.6 cm) AHAM* – 15 3/8" (39.1 cm)
Oven Volume	Overall – 4.0 cu. ft. AHAM* – 3.3 cu. ft.
Approximate Shipping Weight	410 lb. (184.5 kg)

 $^{{}^{\}star}$ The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.





Viking Range Corporation • 111 Front Street • Greenwood, Mississippi 38930 USA • (662) 455-1200 For product information, call 1-888-VIKING1 (845-4641), or visit the Viking website at vikingrange.com.

© 2012, Viking Range Corporation • Specifications subject to change without notice.

F60171D 0113