

BUILT-IN FRENCH-DOOR REFRIGERATOR

Functional styling for your refrigerator.







FRENCH-DOOR REFRIGERATOR FEATURES

Electronic Control Features

- Electronic controls with digital temperature readout maintain the selected temperature in both refrigerator and freezer compartments
- Max Cold™ feature sets refrigerator and freezer temperature to lowest setting
- Adaptive defrost controls the timing of the defrost periods instead of an electromechanical defrost timer and helps prevent freezer burn
- Door open alarm warns when door has been ajar for five minutes
- Water filter indicator light illuminates when water filter needs replacing

Adiustable ColdZone™ Drawers

- Two drawers offer adjustable temperature controls with settings that include Deli, Produce, Meats, and Quick Chill
- Allows storage of foods 3-5 degrees colder than main compartment
- Additional storage in two crisper drawers for preserving fruits and vegetables

Maximizing Storage

- Two adjustable glass Spillproof Plus™ Shelves with Nano technology create an invisible barrier to contain spills
 - Seamless glass shelves make cleanup easy and maximize usable space
 - 3/8" thick tempered glass shelves provide industry leading durability
- Two in-the-door utility bins with covers
- Six adjustable door bins; two with gallon storage
- Base grille water filtration system provides filtered ice without taking up refrigerator space

The Industry's Best and Most Comprehensive Warranty

- 3-year full complete product
- 6-year full sealed refrigeration system
- 12-year limited sealed refrigeration system



SPECIFICATIONS

42"W. FRENCH-DOOR REFRIGERATOR	
Description	VTB5420
Overall width	42-3/8" (107.3 cm)
Overall height from bottom	83-3/8" (211.8 cm) min. to 84-1/2" (214.6 cm) max.
Overall depth from rear	To back of top grille: 23-1/2" (59.7 cm) To front of top grille: 25-3/8" (64.5 cm)
Cutout width	41-1/2" (105.4 cm) min. to 41-3/4" (106 cm) max.
Cutout height	83-1/2" (212.1 cm) min. to 84-3/4" (215 cm) max.
Cutout depth	24" (61.0 cm) min.
Electrical requirements	115 volt, 60 Hz, 15 amp dedicated circuit; 3-wire 84" (213.4 cm) cord with grounded 3-prong plug attached to product
Maximum amp usage	9.9 amps
Inlet water requirements	1/4" copper tubing inlet waterline; 1/4" copper tubing inlet waterline; minimum 20 psi; maximum 120 psi minimum 35 psi; maximum 120 psi
Overall interior dimensions Refrigerator Freezer Total capacity	16.7 cu. ft. (473 liters) 5.9 cu. ft. (167 liters) 22.6 cu. ft. (640 liters)
Approximate shipping weight	550 lbs. (249.5 kg)



