# DISHWASHER FDW300 – 24" WIDE DISHWASHER FDW300WS – 24" WIDE DISHWASHER WITH WATER SOFTENER



### Multi-Level Variable Pressure Washing

- Variable pressure wash adjusts water volume, pressure, and temperature according to load size and soil levels
- Multi-level washing with three spray arms ensures clean dishes
- Turbidity sensor monitors the soil level of the dishes
- Triple filtration system removes the smallest particles for clean water circulation
- Flow-through water heater is concealed to provide a safer alternative to exposed heaters

### Turbo Fan Dry

• Fan circulates air for efficient drying performance

### Quiet Clean™ Performance Package – 48 dB

• Three layers of insulation – bitumen, cotton, and full side walls create one of the quietest dishwashers on the market

#### Loading

- Accommodates 14 international place settings
- Two position adjustable heavy-duty upper rack allows for taller glasses in upper rack or larger pans in bottom rack
- Two stemware cradles/cup shelves
- Adjustable tines
- Heavy-duty lower rack four rows adjustable tines for easy loading of pans
- One-piece silverware/cutlery basket
- Removable upper-third rack for large cutlery and utensils



#### Built-In Water Softener (FDW300WS model)

• Reduces water hardness to a manageable level to prevent glasses and dishes from etching

## Cycles/Options

- Cycles
- Pots/Pans Plus
- Pots/Pans
- Normal Wash
- Light/China
- Fast Wash
- Rinse/Hold
- Options
- Half Load
- Tablet Function
- Delay Start (up to 9.5 hours)
- Sanitize
- LCD screen with remaining time indicator
- Energy Star Qualified

#### **Finishes**

- Available in Custom Panel Model (no front)
- Optional Door Panels (RVDP324) available in Stainless Steel (SS), Black (BK), and White (WH)



- Three-year full complete product
- Ninety-day full cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited tank and inner door
- Five-year limited electronic controls, racks, motor/pump assemblies and water distribution system



DESCRIPTION	24" WIDE DISHWASHER
	FDW300/FDW300WS
Overall Width	23 9/16" (59.8 cm)
<b>Overall Height from Floor</b>	33 7/8" (86.0 cm) minimum to 35 7/8" (91.1 cm) maximum
Overall Depth from rear Without Door Panel With Door Panel	21 5/8" (54.9 cm) 22 3/16" (56.4 cm)
Cutout Width	24" (61.0 cm)
Cutout Height	34" (86.4 cm) minimum to 36" (91.4 cm) maximum
Cutout Depth	24" (61.0 cm)
Electrical Requirements	12.0 amps, 115V60Hz; 4' (120 cm) electrical cord supplied with unit
Water Heating Element Rating	1,240 watts
Inlet Water Temperature	120°F (49°C) required
Drain Hose	6.4' (1.9m) drain hose provided
Drain Hose High Loop Required	Height from floor – 28" (71.0 cm)
Approximate Shipping Weight	97 lbs. (44kg)





Viking Range, LLC | 1-888-845-4641 or 662-455-1200 For detailed product information, model numbers, or to request a quote visit vikingrange.com © 2013 Viking Range, LLC | Specifications subject to change without notice.