

INCOGNEETO INDUCTION WARMER

Viking 5 Series - VUIW

TRUE COMMERCIAL TECHNOLOGY FOR THE HOME

- Offers four selectable temperature settings: 150°/160°/175°/190°F (65°/70°/80°/85°C)
- 650 watts of power
- The Magneeto™ II trivet-like device is used on the upper surface of the countertop to locate the heat zone and acts as a temperature sensor
- Touch control user interface with SmarTag™ Technology uses a wireless communicator to provide precise temperature control
- Cookware/bakeware up to a diameter of approximately 12" (30.5 cm) with an induction compatible base can be used
- Automatic pan detection allows for instant energy transmission to pan and no energy transmission when pan is not present
- Can combine up to three units per 15 amp circuit



- A beautiful piece of natural stone or "engineered stone" can transform into an induction warmer capable of holding food within 2°F
- Designed to be mounted directly under stone or engineered stone countertops
- The unit mounts underneath the counter with no drilling or cutting of the stone required
- Compatible with all natural and engineered stones
- 1-1/4" thick with no substrate
- 3/4" thick with 1/2" -3/4" plywood substrate

MODEL NUMBERS

■ VUIW518 – 18"W. Undercounter Induction Warmer





COLOR FINISHES

 Stainless housing with black glass (unit to be hidden under countertop)

WARRANTY

- ■1-year full covers complete unit
- 90-day full cosmetic parts such as glass, painted items, and decorative items



INCOGNEETO INDUCTION WARMER

Viking 5 Series – VUIW

INCOGNEETO™ INDUCTION WARMER				
DESCRIPTION	VUIW518			
Dimensions	17.5" × 17.5" × 4.5" (44.5 × 44.5 × 11.4 cm)			
Power Range	Range 100-650W			
Amperage	5A (max)			
Voltage	100-120VAC, 50/60 Hz			
Power Requirements	100-120VAC, 1Ph			
Preset Temperatures	Temperatures 150, 160, 175, 190°F/65, 70, 80, 85°C			
Approximate Shipping Weight	proximate Shipping Weight 20 lb. (9 kg)			

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.

	Dimensions	I '	A
А	17-1/2" (4.5 cm)		
В	4-1/2" (1.8 cm)		
С	2-7/8" (7.4 cm)		
D	2-1/4" (5.7 cm)		
E	3-1/4" (8.3 cm)		
F	1-3/16" (3.0 cm)	12/34	♦ • • • • • • •
G	2-1/2" (6.3 cm)		
н	3-13/16" (9.7 cm)		
ı	1" (2.5 cm)	1 3	
		F G H	
6ft (1.8M) Power Cord 7ft (2.1M) Control Cable			8 8



VIKING RANGE, LLC 111 FRONT STREET GREENWOOD, MISSISSIPPI 38930 USA

For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2020 Viking Range, LLC All rights reserved. Specifications subject to change without notice.

F60380A